THIS SIDE TO BE COMPLETED BY APPLICANT

APPLICATION FOR PERMIT TO MAKE EXCAVATION AND /OR FILL OR TO INSTALL CULVERT ON COUNTY TRUNK HIGHWAYS

In as much as Chapter 86.07 (2) of the State Statutes states that "no person shall make any excavation or fill or install any culvert. In any highway. Without a permit therefor from the highway authority maintaining the highway...," the undersigned requests a permit for the purpose of:

Located on	the (north-south-east-we	est) side of (C. T. H.):	located
	(miles-feet)	(north-south-east-west)	junction with (U.S.H-C.T.HS.T.H
Town Road)		_in the (NW-NE-SW-SE) 1/4	4 of Section
Township		North, Range	East, (Town-City-Village) of
		_in	County.
Approximate	e starting date	Approximate comp	letion date
_	ific use of land that dri , service station, wareho	veway will serve (i.e., ouse, etc.)	residence, agricultural,
-	SHALL PLACE FLAG OR MARKE F THE PROPOSED WORK.	R IN THE HIGHWAY DITCH VI	ISIBLE FROM THE HIGHWAY AT THE
		LOCAL ZONING AUTHORITY. I	INSTALLATION WITHOUT THEIR
	gation and field inspecti in company with the appl		esentative of the County Highway
Signed			MAIL COMPLETED APPLICATION TO:
	Applicant (owner of Pro	operty)	
	(Print name plainly)		FOREST COUNTY HIGHWAY DEPT. 5350 COUNTY ROAD W CRANDON, WI 54520
Date			
Address			
	(Where permit can be ma	ailed for signature)	
	Number e applicant can be reache s pertaining to the pro		

TO BE SIGNED BY THE FOREST COUNTY ZONING ADMINISTRATOR

TO BE COMPLETED BY THE FOREST COUNTY HIGHWAY COMMISSIONER Date Checked By Existing culvert pipe size, length and condition: Number Type Required Culvert Pipe Size a. NC C R U new driveway b. NC C R U additional driveway c. NC C R U widened driveway d. NC C R U relocated driveway e. NC C R U present driveway c. Dustify number of driveways (if more than one; additional driveway; reason for relocation, etc) DRIVEWAY MEASUREMENTS: Top width at R/W radius return Depth ditch to top of Driveway Depth ditch to top of Driveway Distance from edge of pavement to ditch line Depth driveway Standard Clauses Required (north-south-east-west) Dristance from edge of pavement to ditch line Radius length STANDARD CLAUSES REQUIRED: Slope Clause Bituminous Clause (Y-N - shoulder maintenance) Plastic Pipe Clause Minor Landscaping clause (improve) Poutre culvert pipe installation clause Relocation Clause (move Feet-miles direction) Raditional clauses Required (attach separate sheet) Widening Clause (from 10	Local Zonir	ng Authority Approval	gnature	Date			
Existing culvert pipe size, length and condition: Number	COMMENTS:		-gnacare				
Existing culvert pipe size, length and condition: Number							
Number Type Required Culvert Pipe Size a. NC C R U new driveway b. NC C R U widened driveway c. NC C R U widened driveway d. NC C R U widened driveway from To Culvert Pipe d. NC C R U relocated driveway e, NC C R U present driveways Culvert Pipe g. NC C R U present driveways Culvert Pipe g. NC C R U present driveways Culvert Pipe If no culvert for a-b-c-d-e- above, state reason why: Dustify number of driveways (if more than one; additional driveway; reason for relocation, etc) DRIVEWAY MEASUREMENTS: VISION OF APPROACHING TRAFFIC Top width at R/W radius return Depth ditch to top of Driveway Distance from edge of pavement to ditch line Radius length Curb and gutter opening width STANDARD CLAUSES REQUIRED: Slope Clause Plastic Pipe Clause Plastic Pipe Clause Minor Landscaping clause (improve Plastic Pipe Clause Minor Landscaping clause (improve Additional clauses Relocation Clause (move Feet-miles direction) Relocation Clause (move Feet-miles direction) Relocation Clause (move Additional clauses Required (attach separate sheet) Widening Clause (from 10 Minimum 25 width at pavement Minimum 25 width at pavement Minimum 25 width at pavement for at least 20'					<u>R</u>		
a. NC C R U new driveway b. NC C R U additional driveway c. NC C R U widened driveway d. NC C R U widened driveway e, NC C R U relocated driveway e, NC C R U present driveways Culvert Pipe e, NC C R U present driveways Culvert Pipe g, NC C R U present driveways Culvert Pipe g, NC C R U present driveways Culvert Pipe g, NC C R U present driveways Culvert Pipe If no culvert for a-b-c-d-e- above, state reason why: DRIVEWAY MEASUREMENTS: VISION OF APPROACHING TRAFFIC Top width at R/W radius return Depth ditch to top of Driveway Distance from edge of pavement to ditch line Radius length Culvert Pipe Culvert Pipe feet (north-south-east-west) Feet (north-south-east-west) Distance from edge of pavement to ditch line Radius length STANDARD CLAUSES REQUIRED: Slope Clause Plastic Pipe Clause Plastic Pipe Clause Plastic Pipe Clause Minor Landscaping clause (improve Plastic Pipe Clause Future culvert pipe installation clause Relocation Clause (move Feet-miles direction) Radditional clauses Required (attach separate sheet) Widening Clause (from To Minimum 2% slope away from pavement for at least 20'	Existing cu	alvert pipe size, length and cond	ition:				
b. NC C R U additional driveway c. NC C R U widened driveway d. NC C R U widened driveway e, NC C R U present driveways To culvert Pipe Culvert Pipe Culvert Pipe Culvert Pipe Culvert Pipe To culvert Pipe Culvert Pipe Culvert Pipe To culvert Pipe Culvert	Number	Туре	Require	ed Culvert Pipe Size			
Top width at R/W radius return Depth ditch to top of Driveway Distance from edge of pavement to ditch line Radius length Curb and gutter opening width STANDARD CLAUSES REQUIRED: Slope Clause Plastic Pipe Clause Minor Landscaping clause (improve) Future culvert pipe installation clause Relocation Clause (move Feet-milesdirection) Required (attach separate sheet) Minimum 25 width at pavement Minimum 25 width at pavement for at least 20'	b. c. d.	_NC C R U additional driveway _NC C R U widened driveway _NC C R U relocated driveway	From	Culve_ _ToCulve_ Culve	ert Pipe ert Pipe ert Pipe		
Top width at R/W radius return Depth ditch to top of Driveway Distance from edge of pavement to ditch line Curb and gutter opening width STANDARD CLAUSES REQUIRED: Slope Clause Bituminous Clause (Y-N - shoulder maintenance) Plastic Pipe Clause Minor Landscaping clause (improve Puture culvert pipe installation clause Relocation Clause (move Feet-miles Required (attach separate sheet) Minimum 25 width at pavement Minimum 25 width at pavement for at least 20'							
Depth ditch to top of Driveway	DRIVEWAY MI	EASUREMENTS:	VISION OF	APPROACHING TRAFFIO			
Slope Clause Bituminous Clause (Y-N - shoulder maintenance) Plastic Pipe Clause Minor Landscaping clause (improve) Future culvert pipe installation clause Underground cable clause Relocation Clause (move Feet-miles direction) Additional clauses Required (attach separate sheet) Widening Clause (fromto) COMMENTS: Minimum 25' width at pavement Minimum 28' slope away from pavement for at least 20'		_Depth ditch to top of Driveway _Distance from edge of pavement t	feet	(north-south-east-w	est)		
Plastic Pipe ClauseMinor Landscaping clause (improve) Future culvert pipe installation clause Underground cable clause Relocation Clause (move Feet-milesdirection) Additional clauses Required (attach separate sheet) Widening Clause (fromto) COMMENTS: Minimum 25' width at pavement Minimum 2% slope away from pavement for at least 20'	STANDARD CI	LAUSES REQUIRED:					
Mínímum 2% slope away from pavement for at least 20'	Relocation	Plastic Pipe ClauseMinoMino	r Landscaping cl clauseUnder rection)	ause (improve) ground cable clauseAdditional c			
	COMMENTS:	Minimum 25' width at pavement					
Dríveway must be 90 degree angle from existing pavement							
		Dríveway must be 90 degree angle from exist	ing pavement				